



Note:

- *  Important Dimension To Check
- * Waterproof Rate: IP68
- * Housing: Nylon+GF, Black
- * Pin: Copper Alloy, Gold Plated
- * Nut: Zinc Alloy, Nickel Plated
- * Gasket: Silicone, Gray
- * Clamp Ring: Nylon, Black
- * Sealing Nut: Nylon, Black
- * Seal: Silicone, Dark Gray
- * Seal For Cable OD: $\varnothing 4.5\text{mm}$ - $\varnothing 6.5\text{mm}$

UNIT:mm		TITLE MI2 D CODE Assy M Conn M PIN			Amphenol LTW 安費諾亮泰企業股份有限公司	ITEM NO	DRAWN BY JC Chen	DATE 2019/08/28
TOLERANCE ± 0.5		SCALE 1:1	SIZE A4	SHEET 1 OF 2		DWG NO MI2D-XXBMM-SL8001	CHECKED BY Li Feng	DATE 2019/08/28
		REV. A	WC-REV. A.5	QC: Inspection item		CUSTOMER ALTW	APPROVED BY Jerry	DATE 2019/08/28

	1	2	3	4	5	6	7	8
F								
E								
D								
C								
B								
A								

ALTW

CONFIDENTIAL

2019-08-28

R&D DEPT.

M 12D - XX B M M A - S L 8 001

12A: D-Code

03: 3Pin

04: 4Pin

05: 5Pin

B: Without S/R(無網尾)

M: Male Connector(公座)

M: Male Pin(公Pin)

001:Without Cable

8: IP68(防水等級68)

L: Straight (180°)

S: Screw(螺紋式)

A: Solder Type

UNIT:mm			TITLE M12 D CODE Assy M Conn M PIN			Amphenol LTW 安費諾亮泰企業股份有限公司		ITEM NO	DRAWN BY JC Chen	DATE 2019/08/28
TOLERANCE ± 0.5			SCALE 1:1	SIZE A4	SHEET 2 OF 2			DWG NO M12D-XXBMMA-SL8001	CHECKED BY Li Feng	DATE 2019/08/28
			REV. A	WC-REV. A.5	QC:Inspection item			CUSTOMER ALTW	APPROVED BY Jerry	DATE 2019/08/28

1

2

3

4

5

6

7

8 W10814-03-2001A2



M 12D - XX B M M A - S L 8 001

001:Without Cable

12A: D-Code

03: 3Pin

04: 4Pin

05: 5Pin

8: IP68(防水等級68)

L: Straight (180°)

S: Screw(螺紋式)

A: Solder Type

B: Without S/R(無網尾)

M: Male Connector(公座)

M: Male Pin(公Pin)