

LIGHT ENGINE COB UVC 24mm x 19mm 280mW


Issue Date	September 2020
Issued by	Malassise, V.

Applications

- Medical sterilization
- Drinking water disinfection
- Infectious disease control
- Food processing sterilization
- Air sterilization

Characteristics

- UV Type - UVC
- Wavelength – 275nm
- Efficacy - up to 2.0%
- L70 > 20,000h
- 05 years warranty



DRIVING CURRENTS

Parameter	Nominal	Max
LIGHT ENGINE COB UVC 24mm x 19mm 280mW	1,000 mA	1,200 mA

MODULE TEMPERATURES

Parameter	Nominal	Max
Ts (temperature at Ts point)	40 °C	60 °C

PRODUCT PART NUMBER

80338100100

UVC – 275 nm

TECHNICAL INFORMATION


UV Type	Wavelength (nm)	#LEDs	Forward Current (mA)	Rad. Power (mW)	Forward Voltage (V)	Power (W)	Ts (°C)	EFF (%)
UVC	275	4	700	224.0	15.0	10.4	40	2.0
			1,000	280.0	16.0	16.0	40	1.8
			1,200	296.0	18.0	21.6	40	1.4

LED TYPE


Manufacturer: Klaran

LED Series: KL265


Rad. Power (mW) x Forward Current (mA) (Ts 40°C)




Forward Voltage (V) x Forward Current (mA) (Ts 40°C)



SCHEMATICS






Unit: mm

WIRING

Specification item	Value	Unit	Condition
Input wire cross- section	0.25...0.75 18...24	mm ² AWG	Solid wire
Input wire strip length	7.5...8.5	mm	Solid wire
Input wire cross-section	0.33...0.5 20...22	mm ² AWG	Stranded wire
Input wire strip length	7.5...8.5	mm	Stranded wire



COMPATIBLE OPTICS

Manufacturer	Part Number	Color	Beam
LEDiL	F15074_ZORYA-SC	Clear	~340°
LEDiL	F14627_STELLA-FRESNEL	Clear	~25°
LEDiL	C16903_ALISE-70-S	Clear	~15°
LEDiL	C16904_ALISE-70-M	Clear	~24°
LEDiL	C16905_ALISE-70-W	Clear	~36°
LEDiL	C16906_ALISE-70-WW	Clear	~60°
LEDiL	C16899_ALISE-110-S	Clear	~15°
LEDiL	C16900_ALISE-110-M	Clear	~24°
LEDiL	C16901_ALISE-110-W	Clear	~36°
LEDiL	C16902_ALISE-110-WW	Clear	~60°

