

COOLPad® CP1020 ULTRA SOFT

Interface pads



Description

COOLPad® is a line of high performance thermal interface pads, developed to address the industry's growing requirements for easy application, low levels of thermal resistance and high conformability, even at the most challenging and uneven surfaces. COOLPad® is specially suitable for applications with low clamping forces between the heat generating component and the heat dissipation surface.



Features

- Low Thermal Resistance
- High Conformability
- Electrically Insulating
- RoHS, Reach and UL 94-V0 compliant"



Applications

- Electronic components like LEDs, CPUs, MOS
- Mobiles, Laptops, Tablets
- Electrical Vehicle Batteries
- Power devices and modules"



Delivery Format

- Sheets of 200x400m
- Die-cut parts"

COOLPad® CP1020

ULTRA SOFT

CELERA
Passion for Technique

Typical Properties

Properties	Standard	Unit	CP1020
Color	-	-	Dark Grey
Carrier Type	-	-	Silicon
Carrier Reinforcement			No
Thickness	ASTM D374	mm (inch)	0,25-5,0 (0,010-0,20)
Density	ASTM D792	g/cm ³	2,30
Thermal Conductivity	ASTM D5470	W/m.k	2,00
Volume Resistance	ASTM D257	ohms.cm	3.1*10 ¹¹
Thermal Resistance (50psi)	ASTM D5470	°C-in ² / W	0,02
Hardness	ASTM D2240	Shore 00	30±5
Thermal Resistance	ASTM D5470	°C	-60 to 200
Dielectric Strength	ASTM D149	kV/mm	> 4,0
Shelf Life	-	-	5 years
Flame Rate	UL 94	-	V0