

HEIDI-M

~25° medium beam

SPECIFICATION:

Dimensions	Ø 21.6 mm
Height	11.7 mm
Fastening	tape, pin
ROHS compliant	yes ⓘ


MATERIALS:

Component	Type	Material	Colour	Finish
HEIDI-M	Single lens	PMMA	clear	
HEIDI-TAPE	Tape	Acrylic foam	black	



ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CA12536_HEIDI-M	Single lens	3264	204	204	11.1
» Box size: 480 x 280 x 300 mm					





See also our general installation guide: www.ledil.com/installation_guide



OPTICAL RESULTS (MEASURED):





LED XHP35 HD
FWHM / FWTM 28.0° / 55.0°
Efficiency 86 %
Peak intensity 3.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED XHP35 HI
FWHM / FWTM 28.0° / 49.0°
Efficiency 94 %
Peak intensity 3.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED XP-G3
FWHM / FWTM 28.0° / 50.0°
Efficiency 94 %
Peak intensity 3.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED XP-L HD
FWHM / FWTM 28.0° / 52.0°
Efficiency 86 %
Peak intensity 2.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:




OPTICAL RESULTS (MEASURED):





LED XT-E
FWHM / FWTM 28.0° / 49.0°
Efficiency 95 %
Peak intensity 3.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED LUXEON A
FWHM / FWTM 29.0° / 49.0°
Efficiency 88 %
Peak intensity 3.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON R
FWHM / FWTM 29.0° / 49.0°
Efficiency 87 %
Peak intensity 3.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED LUXEON Rebel
FWHM / FWTM 27.0° / 44.0°
Efficiency 88 %
Peak intensity 3.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:





OPTICAL RESULTS (MEASURED):





LED LUXEON Rebel ES
FWHM / FWTM 29.0° / 47.0°
Efficiency 88 %
Peak intensity 3.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED SST-10-B130
FWHM / FWTM 28.0° / 46.0°
Efficiency 94 %
Peak intensity 3.6 cd/lm
LEDs/each optic 1
Light colour Blue
Required components:



LED NVSW219D
FWHM / FWTM 28.0° / 50.0°
Efficiency 94 %
Peak intensity 3.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED NVSW319B
FWHM / FWTM 28.0° / 51.0°
Efficiency 94 %
Peak intensity 3.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:





OPTICAL RESULTS (MEASURED):





LED NVSW3x9A
FWHM / FWTM 28.0° / 51.0°
Efficiency 92 %
Peak intensity 2.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED NVSW519A
FWHM / FWTM 29.0° / 54.0°
Efficiency 94 %
Peak intensity 2.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED NWSx229A
FWHM / FWTM 27.0° / 52.0°
Efficiency 85 %
Peak intensity 2.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED OSLOM SSL 150
FWHM / FWTM 27.0° / 43.0°
Efficiency 88 %
Peak intensity 3.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:




OPTICAL RESULTS (MEASURED):

 SEOUL SEMICONDUCTOR LED Z5M3 FWHM / FWTM 28.0° / 50.0° Efficiency 94 % Peak intensity 3.1 cd/lm LEDs/each optic 1 Light colour White Required components:		
 SEOUL SEMICONDUCTOR LED Z8Y22P FWHM / FWTM 27.0° / 50.0° Efficiency 93 % Peak intensity 3.1 cd/lm LEDs/each optic 1 Light colour White Required components:		


OPTICAL RESULTS (SIMULATED):



LED XP-G2 HE
FWHM / FWTM 30.0° / 51.0°
Efficiency 93 %
Peak intensity 3.1 cd/Im
LEDs/each optic 1
Light colour White
Required components:




LED LUXEON HL2Z
FWHM / FWTM 28.0° / 48.0°
Efficiency 94 %
Peak intensity 3.6 cd/Im
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON IR Domed 150 (L110-0xxx1500000000)
FWHM / FWTM 27.0° / 44.0°
Efficiency 93 %
LEDs/each optic 1
Light colour White
Required components:




LED LUXEON SunPlus 20 Line (120 deg)
FWHM / FWTM 29.0° / 47.0°
Efficiency 96 %
Peak intensity 3.8 cd/Im
LEDs/each optic 1
Light colour White
Required components:



OPTICAL RESULTS (SIMULATED):


LUMILEDS

LED LUXEON SunPlus 20 Line (150 deg)
FWHM / FWTM 28.0° / 46.0°
Efficiency 92 %
Peak intensity 3.8 cd/Im
LEDs/each optic 1
Light colour White
Required components:




LUMILEDS

LED LUXEON SunPlus 20 Line (150 deg)
FWHM / FWTM 28.0° / 44.0° + 46.0°
Efficiency 92 %
Peak intensity 3.8 cd/Im
LEDs/each optic 1
Light colour White
Required components:




LUMILEDS

LED LUXEON SunPlus 35 Line
FWHM / FWTM 28.0° / 46.0°
Efficiency 94 %
Peak intensity 3.9 cd/Im
LEDs/each optic 1
Light colour White
Required components:



LUMILEDS


LED LUXEON TX
FWHM / FWTM 28.0° / 48.0°
Efficiency 94 %
Peak intensity 3.6 cd/Im
LEDs/each optic 1
Light colour White
Required components:




OPTICAL RESULTS (SIMULATED):




LED LUXEON Z ES
FWHM / FWTM 28.0° / 45.0°
Efficiency 94 %
Peak intensity 4 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED NCSxE17A
FWHM / FWTM 28.0° / 57.0°
Efficiency 86 %
Peak intensity 2.4 cd/lm
LEDs/each optic 4
Light colour White
Required components:



LED NV4WB35AM
FWHM / FWTM 28.0° / 52.0°
Efficiency 94 %
Peak intensity 3.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED NVSxE21A
FWHM / FWTM 28.0° / 47.0°
Efficiency 94 %
Peak intensity 3.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:




OPTICAL RESULTS (SIMULATED):

OSRAM

Opto Semiconductors


LED	OSCONIQ P 3737 Flat
FWHM / FWTM	28.0° / 50.0°
Efficiency	95 %
Peak intensity	3.4 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



OSRAM

Opto Semiconductors

LED	OSLON Black Flat (LUW HWQP)
FWHM / FWTM	29.0° / 45.0°
Efficiency	94 %
Peak intensity	3.8 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)