

FLORENCE-1R-Z60


~60° + 110° medium beam

SPECIFICATION:

Dimensions	19.5 x 286.0 mm
Height	7.6 mm
Fastening	clips
ROHS compliant	yes ⓘ


MATERIALS:

Component	Type	Material	Colour	Finish
FLORENCE-1R-Z60	Linear lens	PMMA	clear	



ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
F14468_FLORENCE-1R-Z60 » Box size: 398 x 298 x 265 mm	165	45	15	7.1




See also our general installation guide: www.ledil.com/installation_guide


OPTICAL RESULTS (MEASURED):





LED CALGD0414-M8W1
 FWHM / FWTM 58.0 + 121.0° / 99.0 + 153.0°
 Efficiency 94 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





LED CALGD0814-M17W1
 FWHM / FWTM 57.0 + 118.0° / 99.0 + 152.0°
 Efficiency 92 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED L0-280024-xxx-C0800-L267
 FWHM / FWTM 65.0 + 107.0° / 107.0 + 148.0°
 Efficiency 93 %
 Peak intensity 0.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED XH-B/G
 FWHM / FWTM 63.0 + 113.0° / 105.0 + 155.0°
 Efficiency 94 %
 Peak intensity 0.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (MEASURED):



LUMILEDS

LED LUXEON 3014
FWHM / FWTM 59.0 + 115.0° / 82.0 + 151.0°
Efficiency 94 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LUMILEDS

LED LUXEON 3020
FWHM / FWTM 55.0 + 117.0° / 96.0 + 151.0°
Efficiency 94 %
Peak intensity 0.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LUMILEDS

LED LUXEON 3030 2D (Round LES)
FWHM / FWTM 57.0 + 114.0° / 97.0 + 150.0°
Efficiency 94 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LUMILEDS



LED LUXEON 3535 2D
FWHM / FWTM 60.0 + 109.0° / 100.0 + 150.0°
Efficiency 94 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:





OPTICAL RESULTS (MEASURED):





LED LUXEON 3535L
 FWHM / FWTM 59.0 + 110.0° / 99.0 + 149.0°
 Efficiency 94 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED MP-2016
 FWHM / FWTM 58.0 + 115.0° / 82.0 + 157.0°
 Efficiency 94 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED NF2x757D
 FWHM / FWTM 59.0 + 114.0° / 101.0 + 152.0°
 Efficiency 94 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





LED NF2x757G
 FWHM / FWTM 56.0 + 111.0° / 98.0 + 150.0°
 Efficiency 93 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





OPTICAL RESULTS (MEASURED):




LED NFSW757H
 FWHM / FWTM 107.0 + 60.0° / 148.0 + 104.0°
 Efficiency 94 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14353_FLORENCE-1R-CLIP-A





LED Duris E5
 FWHM / FWTM 112.0 + 58.0° / 149.0 + 99.0°
 Efficiency 94 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED Duris S5 (2 chip)
 FWHM / FWTM 58.0 + 114.0° / 100.0 + 154.0°
 Efficiency 94 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





LED Fortimo LED Line 1ft HF 1R HV5
 FWHM / FWTM 112.0 + 58.0° / 151.0 + 101.0°
 Efficiency 97 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14353_FLORENCE-1R-CLIP-A



OPTICAL RESULTS (MEASURED):



PHILIPS

LED Fortimo LED Line 1ft MF 1R HV5 & LV5
 FWHM / FWTM 112.0 + 59.0° / 151.0 + 100.0°
 Efficiency 97 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14353_FLORENCE-1R-CLIP-A





SAMSUNG

LED LM28xB Series
 FWHM / FWTM 111.0 + 59.0° / 150.0 + 101.0°
 Efficiency 94 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14409_FLORENCE-1R-CLIP-B




SAMSUNG

LED LM28xB Series
 FWHM / FWTM 57.0 + 113.0° / 98.0 + 150.0°
 Efficiency 94 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



SAMSUNG


LED LM301A
 FWHM / FWTM 56.0 + 113.0° / 98.0 + 151.0°
 Efficiency 94 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (MEASURED):


SAMSUNG

LED LM302A
FWHM / FWTM 59.0 + 111.0° / 99.0 + 151.0°
Efficiency 94 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:





SAMSUNG

LED LM561B
FWHM / FWTM 59.0 + 111.0° / 100.0 + 151.0°
Efficiency 94 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:





SAMSUNG

LED LM561B Plus
FWHM / FWTM 117.0 + 58.0° / 151.0 + 100.0°
Efficiency 94 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C14353_FLORENCE-1R-CLIP-A



SAMSUNG



LED LM561C
FWHM / FWTM 56.0 + 113.0° / 98.0 + 149.0°
Efficiency 94 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OPTICAL RESULTS (MEASURED):



SAMSUNG

LED LT-S282N
 FWHM / FWTM 56.0 + 112.0° / 99.0 + 149.0°
 Efficiency 94 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





SEOUL SEMICONDUCTOR

LED SEOUL 3030
 FWHM / FWTM 59.0 + 111.0° / 98.0 + 150.0°
 Efficiency 94 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



SEOUL SEMICONDUCTOR


LED SEOUL DC 3030
 FWHM / FWTM 115.0 + 55.0° / 150.0 + 98.0°
 Efficiency 94 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C14353_FLORENCE-1R-CLIP-A




OPTICAL RESULTS (SIMULATED):




LED LUXEON 2835 Line
FWHM / FWTM 59.0 + 107.0° / 86.0 + 146.0°
Efficiency 94 %
Peak intensity 0.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED LUXEON 5050 Round LES
FWHM / FWTM 61.0 + 107.0° / 103.0 + 146.0°
Efficiency 94 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:



Opto Semiconductors
LED Duris E 2835
FWHM / FWTM 61.0 + 107.0° / 95.0 + 147.0°
Efficiency 94 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:




Opto Semiconductors
LED Duris E5
FWHM / FWTM 108.0 + 58.0° / 144.0 + 88.0°
Efficiency 75 %
Peak intensity 0.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C14593_FLORENCE-1R-SHD-BLK



OPTICAL RESULTS (SIMULATED):


OSRAM Opto Semiconductors

LED OSCONIQ C 2424
FWHM / FWTM 112.0 + 61.0° / 146.0 + 83.0°
Efficiency 96 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:



SEOUL SEMICONDUCTOR

LED SEOUL DC 3030C
FWHM / FWTM 107.0 + 62.0° / 147.0 + 94.0°
Efficiency 95 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)