

## HB-2X2MX-8-WWW

~65° wide beam. New revision.

### TECHNICAL SPECIFICATIONS:


|                            |                |
|----------------------------|----------------|
| Dimensions                 | 90.0 x 90.0 mm |
| Height                     | 16.4 mm        |
| Fastening                  | screw          |
| Ingress protection classes | IP67           |
| ROHS compliant             | yes ⓘ          |


### MATERIAL SPECIFICATIONS:

| Component           | Type       | Material | Colour | Finish |
|---------------------|------------|----------|--------|--------|
| HB-2X2MX-8-WWW      | Multi-lens | PMMA     | clear  |        |
| STRADA-2X2MX-8-SEAL | Seal       | Silicone | clear  |        |

### ORDERING INFORMATION:

| Component                      |            | Qty in box | MOQ | MPQ | Box weight (kg) |
|--------------------------------|------------|------------|-----|-----|-----------------|
| CS15765_HB-2X2MX-8-WWW         | Multi-lens | 156        | 52  | 52  | 8.4             |
| » Box size: 480 x 280 x 300 mm |            |            |     |     |                 |







See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)

#### PHOTOMETRIC DATA (MEASURED):


##### CREE LED

LED CXA/B 15xx  
FWHM / FWTM 62.0° / 123.0°  
Efficiency 92 %  
Peak intensity 0.7 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:  
Bender Wirth: 441 Typ 2x2MX HV





##### CREE LED

LED XHP50.2  
FWHM / FWTM 80.0° / 121.0°  
Efficiency 94 %  
Peak intensity 0.5 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





##### CREE LED

LED XT-E HE  
FWHM / FWTM 68.0° / 114.0°  
Efficiency 94 %  
Peak intensity 0.7 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



##### LUMILEDS


LED LUXEON M/MX  
FWHM / FWTM 82.0° / 119.0°  
Efficiency 94 %  
Peak intensity 0.5 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





#### PHOTOMETRIC DATA (MEASURED):




LED LUXEON XR-7070  
 FWHM / FWTM 72.0° / 110.0°  
 Efficiency 95 %  
 Peak intensity 0.6 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





LED NV9W149AM  
 FWHM / FWTM 81.0° / 130.0°  
 Efficiency 94 %  
 Peak intensity 0.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



LED PrevaLED Brick HP 2x2MX  
 FWHM / FWTM 71.0° / 111.0°  
 Efficiency 93 %  
 Peak intensity 0.6 cd/lm  
 LEDs/each optic 4  
 Light colour White  
 Required components:





LED HiLOM SC16 (LH181B)  
 FWHM / FWTM 65.0° / 103.0°  
 Efficiency 94 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### PHOTOMETRIC DATA (MEASURED):



##### SCIOLUX

LED XLE-S22C4XD16 (XD16)  
 FWHM / FWTM 74.0° / 112.0°  
 Efficiency 94 %  
 Peak intensity 0.5 cd/lm  
 LEDs/each optic 4  
 Light colour White  
 Required components:





##### SCIOLUX

LED XLE-S22C4XTEHE (XT-E HE)  
 FWHM / FWTM 68.0° / 114.0°  
 Efficiency 94 %  
 Peak intensity 0.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





##### SCIOLUX

LED XLE-S22XHP50B (XHP50.2)  
 FWHM / FWTM 80.0° / 121.0°  
 Efficiency 94 %  
 Peak intensity 0.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



SEOUL SEMICONDUCTOR


LED Z8Y22  
 FWHM / FWTM 68.0° / 108.0°  
 Efficiency 94 %  
 Peak intensity 0.6 cd/lm  
 LEDs/each optic 4  
 Light colour White  
 Required components:



#### PHOTOMETRIC DATA (SIMULATED):




LED Bridgelux SMD 5050  
 FWHM / FWTM 78.0° / 105.0°  
 Efficiency 94 %  
 Peak intensity 0.6 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### CITIZEN

LED CLU700/701/702  
 FWHM / FWTM 66.0° / 98.0°  
 Efficiency 92 %  
 Peak intensity 0.8 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 Bender Wirth: 434 Typ 2x2MX HV




LED XHP70.2  
 FWHM / FWTM 86.0° / 122.0°  
 Efficiency 89 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:

Protective plate, glass




LED XHP70.3 HD  
 FWHM / FWTM 86.0° / 120.0°  
 Efficiency 95 %  
 Peak intensity 0.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### PHOTOMETRIC DATA (SIMULATED):


##### LUMILEDS

LED LUXEON 5050 Round LES  
FWHM / FWTM 78.0° / 102.0°  
Efficiency 97 %  
Peak intensity 0.6 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




##### LUMILEDS

LED LUXEON 7070  
FWHM / FWTM 75.0° / 108.0°  
Efficiency 96 %  
Peak intensity 0.7 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




##### LUMINUS

LED SFT-40-WCS  
FWHM / FWTM 82.0° / 94.0°  
Efficiency 97 %  
Peak intensity 0.6 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



##### LUMINUS


LED SFT-70X-WCS  
FWHM / FWTM 82.0° / 98.0°  
Efficiency 97 %  
Peak intensity 0.5 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




### PHOTOMETRIC DATA (SIMULATED):




LED NFMW48xA  
FWHM / FWTM 79.0° / 106.0°  
Efficiency 94 %  
Peak intensity 0.6 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED NV4WB35AM  
FWHM / FWTM 80.0° / 102.0°  
Efficiency 96 %  
Peak intensity 0.5 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED OSCONIQ P 7070  
FWHM / FWTM 82.0° / 112.0°  
Efficiency 96 %  
Peak intensity 0.5 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)