

MOLLY-W

~60° wide beam


TECHNICAL SPECIFICATIONS:

Dimensions	Ø 69.8 mm
Height	22.1 mm
Fastening	
Colour	clear
Box size	476 x 273 x 292 mm
Box weight	8.1 kg
Quantity in Box	198 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:



Component	Type	Material	Colour
MOLLY-W	Single lens	PMMA	clear





PHOTOMETRIC DATA (MEASURED):





LED Vero SE 13
FWHM 62.0°
Efficiency 90 %
Peak intensity 0.860 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C16402_CLAMP-VEROSE-13-18



LED Vero SE 18
FWHM 62.0°
Efficiency 90 %
Peak intensity 0.810 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C16402_CLAMP-VEROSE-13-18




LED Vesta TW 15mm DP
FWHM 61.0°
Efficiency 90 %
Peak intensity 0.847 cd/lm
LEDs/each optic 1
Light colour Tunable White
Required components:
C13658_CLAMP-VERO13-18
Bender Wirth: 482 Typ L2



CITIZEN


LED CLL03x/CLU03x
FWHM 61.0°
Efficiency 89 %
Peak intensity 0.850 cd/lm
LEDs/each optic 1
Light colour White
Required components:
Bender Wirth: 433 Typ L1



PHOTOMETRIC DATA (MEASURED):



CITIZEN

LED CLL03x/CLU03x
FWHM 58.0°
Efficiency 90 %
Peak intensity 0.930 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C16791_CLAMP-Z45-A
TE: 2325807-3





CITIZEN

LED LCN-C02B (Tunable White)
FWHM 62.0°
Efficiency 89 %
Peak intensity 0.900 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13658_CLAMP-VERO13-18
Bender Wirth: 481 Typ L2




CREE

LED CMA1840
FWHM 64.0 + °
Efficiency 91 %
Peak intensity 0.820 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C14123_CLAMP-CXA15-18



CREE



LED CMA2550
FWHM 63.0°
Efficiency 89 %
Peak intensity 0.770 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C14036_CLAMP_CXA25-30





PHOTOMETRIC DATA (MEASURED):





LED CMA3090
FWHM 64.0°
Efficiency 89 %
Peak intensity 0.750 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C14036_CLAMP_CXA25-30





LED CMT14xx
FWHM 60.0°
Efficiency 90 %
Peak intensity 0.900 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13658_CLAMP-VERO13-18
Bender Wirth: 434 Typ L1



LED CMT19xx
FWHM 61.0°
Efficiency 90 %
Peak intensity 0.831 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13658_CLAMP-VERO13-18
Bender Wirth: 477 Typ L1





LED CMT28xx
FWHM 61.0°
Efficiency 88 %
Peak intensity 0.800 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13584_CLAMP-VERO29
Bender Wirth: 471 Typ L3





PHOTOMETRIC DATA (MEASURED):





LED CXA/B 15xx
FWHM 61.0°
Efficiency 90 %
Peak intensity 0.870 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C14123_CLAMP-CXA15-18





LED LUXEON CoB 1204HD
FWHM 57.0°
Efficiency 89 %
Peak intensity 0.960 cd/lm
LEDs/each optic 1
Light colour White
Required components:
TE: 2213382-2 + OPTIC CLIP Z50 TYPE1 2213194-1



LED CDM-14 (Dim-To-Warm)
FWHM 64.0°
Efficiency 89 %
Peak intensity 0.800 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13658_CLAMP-VERO13-18
Bender Wirth: 491 Typ L2




LED CDM-18 (Dim-To-Warm)
FWHM 63.0°
Efficiency 89 %
Peak intensity 0.800 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13658_CLAMP-VERO13-18
Bender Wirth: 491 Typ L2




PHOTOMETRIC DATA (MEASURED):





LED CDM-9 (Dim-To-Warm)
FWHM 61.0°
Efficiency 89 %
Peak intensity 0.860 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13658_CLAMP-VERO13-18
Bender Wirth: 490 Typ L1





LED CTM-14 (Tunable White)
FWHM 62.0°
Efficiency 88 %
Peak intensity 0.830 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13584_CLAMP-VERO29
Bender Wirth: 442 Typ L3



LED CTM-22 (Tunable White)
FWHM 62.0°
Efficiency 87 %
Peak intensity 0.700 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13584_CLAMP-VERO29
Bender Wirth: 494 Typ L3





LED NVCWJ024Z-V1MT: COB J-Type Tunable White
FWHM 60.0°
Efficiency 89 %
Peak intensity 0.900 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13658_CLAMP-VERO13-18
Bender Wirth: 498 Typ L2



PHOTOMETRIC DATA (MEASURED):


OSRAM

LED PrevaLED Core G7 L15 H1
FWHM 57.0°
Efficiency 90 %
Peak intensity 0.950 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C16685_CLAMP-PRV-A





PHILIPS

LED Fortimo SLM L13 CoB
FWHM 60.0°
Efficiency 89 %
Peak intensity 0.900 cd/lm
LEDs/each optic 1
Light colour White
Required components:
TE: 2213130-2 + OPTIC CLIP Z50 TYPE1 2213194-1





PHILIPS

LED Fortimo SLM L15 + SLM holder
FWHM 57.0°
Efficiency 89 %
Peak intensity 0.900 cd/lm
LEDs/each optic 1
Light colour White
Required components:
TE: OPTIC CLIP Z50 TYPE1 2213194-1



PHILIPS


LED Fortimo SLM L15 CoB
FWHM 60.0°
Efficiency 88 %
Peak intensity 0.900 cd/lm
LEDs/each optic 1
Light colour White
Required components:
TE: 2213130-2 + OPTIC CLIP Z50 TYPE1 2213194-1



PHOTOMETRIC DATA (MEASURED):



SAMSUNG

LED LC035T (Tunable white)
FWHM 62.0°
Efficiency 89 %
Peak intensity 0.793 cd/lm
LEDs/each optic 1
Light colour Tunable White
Required components:
C13584_CLAMP-VERO29
Bender Wirth: 502 Typ L3



XICATO

LED XTM - 19mm LES
FWHM 60.0°
Efficiency 90 %
Peak intensity 0.880 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C16491_XTM-ADAPTER-50-A




PHOTOMETRIC DATA (SIMULATED):



LED V9 HD
FWHM 58.0°
Efficiency 90 %
Peak intensity 1.035 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13658_CLAMP-VERO13-18
Bender Wirth: 496 Typ L1




LED VERO13
FWHM 55.0°
Efficiency 90 %
Peak intensity 1.100 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13658_CLAMP-VERO13-18




CITIZEN

LED CLL02x/CLU02x (LES10)
FWHM 54.0°
Efficiency 89 %
Peak intensity 1.190 cd/lm
LEDs/each optic 1
Light colour White
Required components:
Bender Wirth: 434 Typ L1




LED CXA/B 1816 & CXA/B 1820 & CXA 1850
FWHM 58.0°
Efficiency 90 %
Peak intensity 1.070 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C14123_CLAMP-CXA15-18



PHOTOMETRIC DATA (SIMULATED):



LED CXA/B 25xx
FWHM 57.0°
Efficiency %
Peak intensity 1.070 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C14036_CLAMP_CXA25-30



LED CTM-18 (Tunable White)
FWHM 54.0°
Efficiency 80 %
Peak intensity 0.992 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13658_CLAMP-VERO13-18

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)